## Industrial level handheld POS SUNMI L2

- 5.0" HD IPS display.
- · High performance quad-core processor
- · 2GB RAM+16GB ROM.
- · Built-in dual card slots; supports 4G full netcom, NFC.
- 1D/2D code scanning; Zebra scanning head is optional.
- · Across industrial and commercial consumption fields.





Scanning

5000mAh rugged design



Optional single charging stand

## SUNMI L2 Technical specifications 2 types of configuration International brand Zebra scanner/no scanner os CPU Display Memory Adapter OS 1 Δ 2GB RAM + 16GB ROM Input: AC 100–240V Output: DC 5V/2A 5" HD 1280×720 SUNMI OS Multi-touch screen Wi–Fi Bluetooth Button Speaker NFC 3 ⊁ 口) 2)) $( \mathbb{D} )$ Support BLE MIFARE/FeliCa/ Power (lock screen) button Support IEEE 802.11 a/b/g/n Support Bluetooth 2.1/3.0/4.2 Volume up/down button ISO 14443 Battery Communication Camera MicroSD (TF) SIM Card Slot $(\bigcirc)$ III (::: 1× SIM card slot Support (up to 64G) Support 1.8V/3.0V lithium battery 3.8V/5000mAh 5.0MP, Flashlight, AF Support 1D/2D Support 720p video recording PSAM Port Environment $\mathbf{(}$ Operating temperature: -20°C ~ 55°C PSAM Storage temperature: -40°C ~ 70°C Protection rating: IP67 Falling height: 1.2 m Optional Scanner

International brand Zebra scanner supporting 1D/2D code scanning

Actual memory will be reduced due to a number of factors and may vary. Operating system also occupies some memory.
<u>2. The actual specs of products launched to the market shall take precedence over the info listed in this catalogue; any change may be made without prior notification.</u>